

Calumet NOVA Soft Box



Size	Dimensions	Part No.
NOVA 22	16 x 22"	RM3122
NOVA 32	24 x 32"	RM3132
NOVA 48	36 x 48"	RM3148
NOVA 72	54 x 72"	RM3172

Contents

Thank you for purchasing your **Calumet Soft Box**. Each soft box is made of high-quality materials and offers many unique features that provide you with a additional light control and versatility.

Contents:



- [A] Five support rods
- [B] One Nova Soft Box
- [C] One front diffuser
- [D] One inner baffle



CALUMET
PHOTOGRAPHIC

www.calumetphoto.com

Calumet NOVA Soft Box



For more information
and listings, visit
calumetphoto.com.

Assembly Instructions

Step 1: Insert the four support rods into the sleeves located on each of the interior corners of the soft box and slide them completely into the pockets at the front of the box. These rods should remain in place even when the soft box is disassembled. Note: Soft box comes with one extra support rod in case one is lost or broken.

Step 2: To attach dedicated light adapter to Calumet Universal Speed Ring or QuickRing (shown above):

A. Remove the four brass nuts and the top washer from QuickRing.

B. Slide the portion of the light adapter that mounts to light source through the QuickRing (as shown) until flanged portion is flat against remaining washers. Then put top washers and brass nuts back into place. Tighten nuts so that there is some tension on the strobe adapter but it still rotates. Different adapters will be required for different lighting options.

Step 3: To attach soft box support rods to Calumet Universal Speed Ring or QuickRing see ring instructions.

Step 4: Attach assembled soft box and mounting ring to the reflector mount on your light source.

Step 5: Your Nova soft box comes with an interior diffuser baffle for additional light diffusion. To install interior baffle, attach the four elastic loops on the corners of the baffle to the metal clips inside of soft box.

Step 6: The front diffuser attaches to the interior-most portion of the Velcro® strip around the front opening of the soft box. Secure the corners first, then close the sides.

Step 7: Secure the Nova's rear cowl snugly around your light source for maximum light efficiency.

Accessories



RD3100

RM6400

Complete Mounting Options

Calumet stocks a wide variety of Speed Ring kits and the more convenient QuickRing with a choice of dedicated mounting adapters to fit all popular lighting units.

CAUTION:

USE WITH FLASH OR COOL LIGHT SOURCE ONLY. USE WITH HOT LIGHTS COULD BE HAZARDOUS. ASSEMBLE SOFT BOX BEFORE ATTACHMENT TO LIGHT SOURCE TO AVOID POSSIBLE DAMAGE TO LAMP OR TUBE. DO NOT DISASSEMBLE SOFT BOX BY PLACING THE UNIT ON THE FLOOR. THIS MAY CAUSE DAMAGE TO THE POCKETS AND THE SUPPORT RODS.